

Interior

PRO-STANDARD 2000 LATEX EGGSHELL WALL PAINT

302-01

8/31/11

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> • A high quality, soft sheen wall paint designed for the professional • Excellent hide • Silky - Smooth-to-the-touch finish • Low odor and fast dry • Spatter resistant • Low VOC formulation (compliant for most areas) 	RECOMMENDED USES <ul style="list-style-type: none"> • Designed for use on interior drywall, plaster, wood, masonry, and primed metal surfaces • Ideal for living rooms, dining rooms, bedrooms, closets and any area where a tough eggshell finish is desired • Not for use on tub or shower stalls, floors, or any surface that will be under water
COLORS 302-01 White 302-93 Mid Tone Base 302-06 Antique White 302-94 Deep Tint Base 302-92 Light Tint Base	FINISH Eggshell VEHICLE Latex Polymer FORMULATION Formulated without lead, chrome and mercury

PHYSICAL DATA (Mixed Components)

GLOSS RATING 2-5%	VISCOSITY 110-112 KU
PERCENT SOLIDS Weight: 50% ± 2.0 Volume: 32% ± 2.0	NET WT/GAL 11.2± 0.25 lbs./gal.
VOC CATEGORY Less than 100 grams/liter	FLASH POINT Higher than 200°F (Setaflash)

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- New masonry should age at least 30 days before being painted.
- A Versa-Seal stain blocking primer is recommended as a first coat on wood containing bleeding extractives (follow label instructions).
- Bare metal must first be primed with a Defi-Rust Acrylic Primer before applying this product (follow label instructions).

RECOMMENDED PRIMERS Drywall 342-66 Pro-Standard 2000 Latex Primer Plaster 342-66 Pro-Standard 2000 Latex Primer Masonry 342-66 Pro-Standard 2000 Latex Primer Wood 342-66 Pro-Standard 2000 Latex Primer Metal 622-XX Defi-Rust Acrylic Metal Primer	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: Up to 10:1 reduction with clean water Airless: As supplied
APPLICATION TEMP. Minimum: 50°F Maximum: 90°F	STORAGE TEMP. Minimum: 50°F Maximum: 90°F
TINTING Bases may be tinted with approved colorants	DRYING TIME (Good Conditions) Tack Free: 1 hr. To Recoat: 2-4 hrs. Hard: 18-24 hrs.
PRACTICAL COVERAGE 300-400 sq. ft./gal. (excludes spray loss) Depending on surface texture and porosity	REDUCTION Apply without thinning (Use small amounts of clean water only if necessary)
RECOMMENDED FILM PER COAT Wet: 4.0-5.3 mils Dry: 1.3-1.7 mils	CLEANUP Soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 302-01 All colors and bases	5 Gallon 1 Gallon 5 Gallon 1 Gallon
FREIGHT CLASS Not regulated	MSDS Available upon request