



TECHNICAL DATA SHEET

PRO-STANDARD 2000

Interior/Exterior

SEMI-GLOSS FILL & FINISH

388-01

08/14/2001A

Formerly 3005

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> A professional quality coating designed to fill, seal, and decorate concrete block in one application. Saves time, labor, and material. Low VOC. Soap & water cleanup. 	RECOMMENDED USES <ul style="list-style-type: none"> Recommended for new unpainted interior or exterior concrete block. Not recommended for use on tub or shower stalls, floors or any surface that will be under water. Do not mix with oil colors, other paints, or solvents.
COLORS 300-01 White	FINISH Semi-Gloss VEHICLE Latex Emulsion FORMULATION Lead, chromate, and mercury free

PHYSICAL DATA

GLOSS RATING 35-40 %	VISCOSITY 115-120 K.U.
PERCENT SOLIDS By weight: 53.9 ± 2.0% By volume: 43.8 ± 2.0%	NET WT. PER GAL. 10.2 ± 0.25 lbs./gal.
VOC CATEGORY 3.2 lbs./gal. (380 grams/liter)	FLASH POINT 142 ° F Closed Cup

SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting.
- New cement surfaces should age at least 30 days before being painted.
- This product should be applied to new block without a primer. Film thickness can be built up to fill voids. If desired, this product may be re-coated with latex paints after 24 hours under good drying conditions.
- Do not apply to block walls that show signs of water seepage.

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: Not recommended Airless: As supplied with 2000 psi pressure & 0.021 mi. tip
APPLICATION TEMPERATURE Minimum: 50 °F. Maximum: 90 °F.	STORAGE TEMPERATURE Minimum: 35 °F. Maximum: 120 °F.
TINTING Not Recommended	DRYING TIME (Good Conditions) Tack free: 6 hrs. To recoat: 24 hrs. Hard: 7 days
PRACTICAL COVERAGE 100-150 sq. ft./gal. (Depending upon the porosity of the substrate)	REDUCTION Not normally recommended. If necessary use small amounts of clean water.
RECOMMENDED FILM PER COAT Wet: 10.0-15.0 mils Dry: 4.5-6.0 mils	CLEAN-UP Clean up with soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	388-01	5 Gallon
FREIGHT CLASS	Non-Flammable Paint	MSDS Available upon request.

HPF-0054, Rev. 1, 8/21/98

A division of the Harrison Paint Co. • P.O. Box 8470 Canton, OH 44711
 Phone: (330) 455-5125 Customer Service: 1-800-321-0680 Fax: (330) 454-1750