

Interior/Exterior

## LATEX FIELD MARKING PAINT

710-01

1/23/17

### PRODUCT CHARACTERISTICS

<b>DESCRIPTION</b> <ul style="list-style-type: none"> <li>• A single component ready-to-spray waterborne coating designed for marking and lining athletic fields.</li> <li>• Ready to apply as supplied means faster job starts, less mess, and more consistent hide and durability than concentrates.</li> <li>• Formulated for airless spraying to provide faster application speed than pump-up type sprayers.</li> <li>• Low VOC formulation (compliant for most areas)</li> </ul>	<b>RECOMMENDED USES</b> <ul style="list-style-type: none"> <li>• Use to mark natural grass and clay playing surfaces.</li> <li>• May be applied on many artificial and synthetic surfaces but adhesion should be tested prior to full application.</li> <li>• Provides a semi-permanent film that is designed to not kill grass or harm soil but can be cut off as grass grows allowing changing of colors and logos.</li> </ul>						
<b>COLORS</b> 710-01 White Other colors available by special order.	<table border="0"> <tr> <td><b>FINISH</b></td> <td>Flat</td> </tr> <tr> <td><b>VEHICLE</b></td> <td>Latex Polymer</td> </tr> <tr> <td><b>FORMULATION</b></td> <td>Formulated without lead, chrome and mercury</td> </tr> </table>	<b>FINISH</b>	Flat	<b>VEHICLE</b>	Latex Polymer	<b>FORMULATION</b>	Formulated without lead, chrome and mercury
<b>FINISH</b>	Flat						
<b>VEHICLE</b>	Latex Polymer						
<b>FORMULATION</b>	Formulated without lead, chrome and mercury						

### PHYSICAL DATA

<table border="0"> <tr> <td><b>GLOSS RATING</b></td> <td>&lt;5%</td> </tr> <tr> <td><b>PERCENT SOLIDS</b></td> <td>Weight: 50% ± 2.0      Volume: 28% ± 2.0</td> </tr> <tr> <td><b>VOC CATEGORY</b></td> <td>Less than 50 grams/liter</td> </tr> </table>	<b>GLOSS RATING</b>	<5%	<b>PERCENT SOLIDS</b>	Weight: 50% ± 2.0      Volume: 28% ± 2.0	<b>VOC CATEGORY</b>	Less than 50 grams/liter	<table border="0"> <tr> <td><b>VISCOSITY</b></td> <td>105-110 KU</td> </tr> <tr> <td><b>NET WT/GAL</b></td> <td>12.1 ± 0.25 lbs./gal.</td> </tr> <tr> <td><b>FLASH POINT</b></td> <td>Higher than 200°F (Setaflash)</td> </tr> </table>	<b>VISCOSITY</b>	105-110 KU	<b>NET WT/GAL</b>	12.1 ± 0.25 lbs./gal.	<b>FLASH POINT</b>	Higher than 200°F (Setaflash)
<b>GLOSS RATING</b>	<5%												
<b>PERCENT SOLIDS</b>	Weight: 50% ± 2.0      Volume: 28% ± 2.0												
<b>VOC CATEGORY</b>	Less than 50 grams/liter												
<b>VISCOSITY</b>	105-110 KU												
<b>NET WT/GAL</b>	12.1 ± 0.25 lbs./gal.												
<b>FLASH POINT</b>	Higher than 200°F (Setaflash)												

### SURFACE PREPARATION & APPLICATION INSTRUCTIONS

<ul style="list-style-type: none"> <li>• Read label directions for detailed instructions and warnings.</li> <li>• Surfaces to be coated must be free of water, dew, frost, and other moisture that would impede adhesion.</li> <li>• Spreading rate is approximately 200 sq. ft. per gallon or about 600-650 lineal feet of 4" line (excludes losses due to spraying). A typical football field requires 7 gallons.</li> <li>• May be applied by brush or roller in small areas.</li> </ul>
---

<b>RECOMMENDED PRIMERS</b> None	<b>RECOMMENDED APPLICATION</b> Brush: As supplied Roller: As supplied Spray: N/A Airless: As supplied
<b>APPLICATION TEMP.</b> Minimum: 50°F      Maximum: 90°F	<b>STORAGE TEMP.</b> Minimum: 50°F      Maximum: 90°F
<b>TINTING</b> May be tinted with up to 4 fl. oz. of approved colorants per gallon.	<b>DRYING TIME (Good Conditions)</b> To Recoat: 1 hour To Play: 1 hour
<b>PRACTICAL COVERAGE</b> 200 sq. ft./gal. (excludes spray loss) (About 600-650 lineal feet of 4" line)	<b>REDUCTION</b> Apply without thinning (Use small amounts of clean water only if necessary)
<b>RECOMMENDED FILM PER COAT</b> Wet: 8.0 mils Dry: 2.2 mils	<b>CLEANUP</b> Soap and water

### PACKAGING AND DISTRIBUTION

<b>STANDARD PACKAGING</b> 710-01	5 Gallon
<b>FREIGHT CLASS</b> Not regulated	<b>SDS</b> Available upon request