Dutch Standard Paints and Specialty Products

TECHNICAL DATA SHEET

Exterior **WOODUCK TRANSLUCENT OIL TONER** **835 Line**

10/1/12

PRODUCT CHARACTERISTICS

DESCRIPTION

- An alkyd modified, oil base toner designed to protect and beautify exterior, bare wood substrates including pine, cedar, redwood, and pressure treated lumber.
- Deep penetrating formulation colors the wood without obscuring the grain or texture.
- Provides a water repellant, UV and mildew resistant dried film.
- High solids / low VOC product (compliant for most areas).

RECOMMENDED USES

- Ideal for decks, shakes and shingles, patio furniture, fences, gazebos, and other wood structures.
- Great for use on properly prepared new or weathered wood surfaces.
- Use for coloring and protecting wood when penetration and minimal hide are desired.

COLORS

835-10 Natural	835-13 True Redwood
835-12 True Cedar	835-14 Heartwood

FINISH	N/A (penetrating product)
VEHICLE	Linseed Oil / Soya Alkyd
FORMULATION	Formulated without lead, chrome and mercury

PHYSICAL DATA

GLOSS RATING	N/A (penetrating product)	**VISCOSITY**	38-44 seconds (#1 Zahn Cup)
PERCENT SOLIDS	Weight: 73% ± 2.0 Volume: 68% ± 2.0	**NET WT/GAL**	7.6 ± 0.25 lbs./gal.
VOC CATEGORY	Less than 250 grams/liter	**FLASH POINT**	114°F (Setaflash)

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous coating failures before applying this product.
- All wood to be coated must be dry (moisture content below 15%) or the toner will not penetrate properly and failure may occur.
- Apply at recommended spreading rates. Applying too thick will cause slow drying, and wrinkling, blistering, peeling or other failure.
- Do not use on non-porous surfaces. This product must penetrate into the substrate.
- The final color achieved will be dependent on the color of the substrate. Application of a small spot of toner in an inconspicuous area is recommended to test for proper penetration and color satisfaction.
- Maintain a wet edge and work to the end of boards to minimize lap marks. When spraying, back-brush the toner to ensure proper penetration.

RECOMMENDED PRIMERS
None

RECOMMENDED APPLICATION

Brush:	As supplied
Roller:	Not recommended
Spray:	As supplied
Airless:	As supplied

APPLICATION TEMP.	Minimum: 50°F Maximum: 90°F	**STORAGE TEMP.**	Minimum: 50°F Maximum: 90°F
TINTING	835-10 natural may be tinted with up to 4 oz of colorant. Other colors can be intermixed.	**DRYING TIME (Good Conditions)**	Tack Free: 12-24 hrs. To Recoat: 15 min. (wet on wet) Light Use: 1-2 days Normal Use: 2-5 days
PRACTICAL COVERAGE	400-600 sq. ft./gal. (smooth surfaces) (Depends on substrate texture and porosity)	**REDUCTION**	Apply without thinning
RECOMMENDED FILM PER COAT	Wet: 2.7-4.0 mils Dry: N/A (penetrating product)	**CLEANUP**	Mineral Spirits

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	All colors	5 Gallon	1 Gallon
FREIGHT CLASS	Combustible Paint	**MSDS**	Available upon request

A division of the Harrison Paint Co. ● 1329 Harrison Ave SW, Canton, OH 44706
Phone: (330) 455-5125 ● Customer Service: 1-800-321-0680 ● Fax: (330) 454-1750