



# TECHNICAL DATA SHEET

Interior

WALL CHARM LATEX EGGSHELL

102-01

06/23/2008

## PRODUCT CHARACTERISTICS

<b>DESCRIPTION</b> • A durable, premium quality, velvety finish wall paint for interior surfaces. Dries to a pleasing low gloss appearance with a soft sheen. Excellent washability. • Low odor / Low VOC & Fast Dry • Available in Hi-Hide base to give one coat coverage in most cases • Soap & water cleanup		<b>RECOMMENDED USES</b> • Recommended for interior drywall, plaster, wood, concrete, and metal that has been properly prepared. • Do not mix with oil colors, other paints, or solvents. • Not recommended for use on tub or shower stalls, floors or any surface that will be under water.	
<b>COLORS</b> 102-01 White            102-03 Oyster White 102-91 HHB            102-05 White Pearl 102-92 LTB            102-06 Antique White 102-93 MTB 102-94 DTB 102-95 CTB		<b>FINISH</b> Eggshell	<b>VEHICLE</b> Latex Emulsion
		<b>FORMULATION</b> Lead, chromate, and mercury free	

## PHYSICAL DATA

<b>GLOSS RATING</b> 6-10 % <b>PERCENT SOLIDS</b> By weight: 53.1 ± 2.0% By volume: 35.6 ± 2.0% <b>VOC CATEGORY</b> 1.3 lbs./gal. (150 grams/liter)	<b>VISCOSITY</b> 98-102 K.U. <b>NET WT. PER GAL.</b> 11.5 ± 0.25 lbs./gal. <b>FLASH POINT</b> >200 ° F Closed Cup
--	---

## SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting.
- New plaster or cement surfaces should age at least 30 days before being painted.
- To maximize holdout and minimize the number of finish coats needed to achieve a uniform appearance, a first coat of the proper primer is recommended. In all cases, bare metal must be primed. Glossy surfaces should be dulled with fine sandpaper and primed with Classic 245 Versa Seal.
- Previously painted surfaces should be cleaned, patched, and spot primed before top coating. Two coats of this product are recommended on most surfaces.

<b>RECOMMENDED PRIMERS</b> Drywall                245-88 Classic Versa Seal Plaster                245-88 Classic Versa Seal Wood                   245-88 Classic Versa Seal Masonry              245-88 Classic Versa Seal Metal                  622-71, -72, -73 Defi-Rust Acrylic Primers Galvanizing          245-88 Classic Versa Seal		<b>RECOMMENDED APPLICATION</b> Brush:                 As supplied Roller:                 As supplied Spray:                 Up to 10:1 reduction with clean water Airless:                As supplied	
<b>APPLICATION TEMPERATURE</b> Minimum: 50 °F. Maximum: 90 °F.		<b>STORAGE TEMPERATURE</b> Minimum: 35 °F. Maximum: 120 °F.	
<b>TINTING</b> Hundreds of additional colors may be obtained by using the tint bases and approved colorants.	<b>DRYING TIME</b> Tack free:        2 hrs. <b>(Good Conditions)</b> To recoat:       4-6 hrs. Hard:              48 hrs.		
<b>PRACTICAL COVERAGE</b> 400 sq. ft./gal. (Depending upon the porosity of the substrate)	<b>REDUCTION</b> Not normally recommended. If necessary use small amounts of clean water. (For spray reduction see recommended application)		
<b>RECOMMENDED FILM PER COAT</b> Wet:                3.0-4.0 mils Dry:                1.0-1.4 mils	<b>CLEAN-UP</b> Clean up with soap and water		

## PACKAGING AND DISTRIBUTION

<b>STANDARD PACKAGING</b> 102-01, 102-91, 102-92, 102-93 102-03 All Other Bases & Colors	5 Gallon    Gallon    Quart 5 Gallon    Gallon    Quart Gallon    Quart
<b>FREIGHT CLASS</b> Non-Flammable Paint	<b>MSDS</b> Available upon request.

HPF-0054, Rev. 1, 8/21/98

Harrison Paint Company • 1329 Harrison Ave SW, Canton, OH 44706  
 Phone: (330) 455-5125 Customer Service: 1-800-321-0680 Fax: (330) 454-1750