



# TECHNICAL DATA SHEET

Interior/Exterior

**OLDE CENTURY COLORS – ACRYLIC LATEX PAINT**

**2000 Series**

9/27/16

## PRODUCT CHARACTERISTICS

<b>DESCRIPTION</b> <ul style="list-style-type: none"> <li>• A waterborne coating formulated with the highest quality ingredients to form a long-lasting protective and decorative finish for interior and exterior surfaces.</li> <li>• Provides a tough, high-hiding, silky-smooth, low sheen finish.</li> <li>• Flexible and breathable dried film resists cracking, peeling, blistering fading, mold and mildew.</li> <li>• Soap and water cleanup.</li> <li>• Low VOC formulation (compliant for most areas).</li> </ul>	<b>RECOMMENDED USES</b> <ul style="list-style-type: none"> <li>• Designed for bare and previously coated wood, plaster, drywall, masonry, and metal substrates that have been properly prepared.</li> <li>• Great for use on trim, furniture, cabinets, walls, doors, railings, primed metal fixtures and many other surfaces.</li> <li>• Also ideal for exterior wood including siding, trim, shutters, fences, gazebos, and masonry such as stucco, cement block, brick, poured and precast concrete, and for primed metal applications.</li> <li>• Not for use on horizontal surfaces where water collects.</li> </ul>				
<b>COLORS (see color card)</b> - Colors may be intermixed to achieve countless additional shades.					
2001 Cranberry	2002 Confederate Red	2003 Cupboard Blue	2004 Yankee Blue	2005 Revere Green	2006 Quaker Green
2007 Olde Ivory	2008 Old Forge Mustard	2009 Union Blue	2010 Brownstone	2011 Tinderbox Brown	2012 Olde Farm White
2013 Windsor Chair Grn	2014 Salt Box Blue	2015 Greenbrier	2016 Olde Navy	2017 Barn Red	2018 Plymouth Blue
2019 Linen White	2020 Thistle	2021 Olde Brick Red	2022 Lamp Black	2023 Olde Pewter	2024 Brierwood Green
2025 Goldenrod Yellow	2026 Manor House Wht	2027 Lantern Glow	2028 Candleberry Grn	2029 Bittersweet	2030 Buttermilk
2031 Fenwick Yellow	2032 Cobblestone	2033 Tavern Yellow	2034 Candlelite	2035 Savanna Red	2036 Olde Sage Green
2037 Firethorn	2038 Salem Gray				

## PHYSICAL DATA

<b>GLOSS RATING</b>	Low Sheen – 5-10%	<b>VISCOSITY</b>	90-94 KU
<b>PERCENT SOLIDS</b>	Weight: Varies by color Volume: 36% ± 2.0	<b>NET WT/GAL</b>	Varies by color
<b>VOC CATEGORY</b>	Less than 150 grams/liter	<b>FLASH POINT</b>	Higher than 200°F (Setaflash)
		<b>FORMULATION</b>	Formulated without lead, chrome, and mercury.

## SURFACE PREPARATION & APPLICATION INSTRUCTIONS

<ul style="list-style-type: none"> <li>• Read label directions for detailed instructions and warnings.</li> <li>• Correct for the cause of any previous paint failures before applying this product.</li> <li>• New masonry should age at least 30 days before being painted.</li> <li>• This product may be applied directly on properly prepared bare wood and masonry.</li> <li>• An appropriate Versa-Seal primer may be used on bare wood and masonry to provide improved holdout and/or stain blocking properties (follow label instructions).</li> <li>• Bare metal must first be primed with a Defi-Rust Acrylic Metal Primer before applying this product (follow label instructions).</li> <li>• 198-4100 Crackle Medium may be added to create an aged appearance (follow label directions).</li> <li>• 198-4200 Chalk Powder may be added to make a chalky coating (follow label directions).</li> </ul>
--

<b>RECOMMENDED PRIMERS</b> Int. Wood: Direct or 240-66 Versa-Seal Undercoater Ext. Wood: 250-77 or 251-77 Versa-Seal Wood Primers Metal: 622-71, 72, 73 Defi-Rust Acrylic Metal Primers Masonry: Direct or 245-88 Versa-Seal Classic Primer Drywall/Plaster: Direct or 245-88 Versa-Seal Classic Primer		<b>RECOMMENDED APPLICATION</b> Brush: As supplied Roller: As supplied Sponge: As supplied or up to 10% reduction with clean water Spray: Up to 10% reduction with clean water Airless: As supplied	
<b>APPLICATION TEMP.</b>	Minimum: 50°F    Maximum: 90°F	<b>STORAGE TEMP.</b>	Minimum: 60°F    Maximum: 80°F
<b>TINTING</b>	Tinting is not recommended. Intermix colors to achieve many additional shades.	<b>DRYING TIME (Good Conditions)</b>	Tack Free: 2-4 hrs. To Recoat: 8-12 hrs. Hard: 48 hrs.
<b>PRACTICAL COVERAGE</b>	400 sq. ft./gal. (Depends on substrate texture, porosity, application method, and thinning)	<b>REDUCTION</b>	Apply without thinning, use small amounts of clean water only if necessary. (See application above)
<b>RECOMMENDED FILM PER COAT</b>	Wet: 3.8-4.2 mils unreduced Dry: 1.4-1.5 mils unreduced	<b>CLEANUP</b>	Soap and water

## PACKAGING AND DISTRIBUTION

<b>STANDARD PACKAGING</b>	All colors	1 Gallon	1 Quart	1 Pint
<b>FREIGHT CLASS</b>	Not regulated	<b>SDS</b>	Available upon request	

A division of the Harrison Paint Co. • 1329 Harrison Ave SW, Canton, OH 44706  
 Phone: (330) 455-5125 • Customer Service: 1-800-222-3092 • Fax: (330) 454-1750