



TECHNICAL DATA SHEET

Interior

OLDE CENTURY COLORS – GEL VARNISH & STAIN

4000 Series

9/28/16

PRODUCT CHARACTERISTICS

<p>DESCRIPTION</p> <ul style="list-style-type: none"> • A low odor, solventborne product designed to color and protect interior wood surfaces all in one product. • Combines high quality pigments with polyurethane resins to form a long-lasting, mar and scratch resistant finish that exhibits a soft, satin appearance. • Gel consistency allows easier working and less dripping than ordinary stains and provides for a more even appearance. • Available in a variety of colors that can be intermixed to make hundreds of additional shades. 	<p>RECOMMENDED USES</p> <ul style="list-style-type: none"> • Specially formulated for easy working on vertical surfaces but is great for horizontal applications as well. • Ideal for furniture, cabinets, doors, trim, paneling, handrails, floors and many other substrates. • May be used on bare wood or over previous coatings to produce an antique finish. • Use with specialized tools to create a wood grain pattern or other distinctive appearance. • Outstanding durability as a finish coat or as a base for clear-coating.
<p>COLORS - Colors may be intermixed to achieve many additional shades.</p> <p>4000 Clear (Use as a pre-seal, clear over-coat or finish, or intermix to weaken other colors)</p> <p>4001 Cherry 4002 Olde Pine 4003 Pecan 4004 Walnut 4005 White</p> <p>4006 Antique (Use as a stain color or as an antiquing liquid)</p>	

PHYSICAL DATA

GLOSS RATING	30-50% (on a sealed surface)	VISCOSITY	Gel
PERCENT SOLIDS	Weight: Varies by color Volume: 33% ± 3.5	NET WT/GAL	Varies by color
VOC CATEGORY	Less than 600 grams/liter	FLASH POINT	119°F (Setaflash)
		FORMULATION	Formulated without lead, chrome, and mercury.

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

<ul style="list-style-type: none"> • Read label directions for detailed instructions and warnings. • Correct for the cause of any previous paint failures before applying this product. • Apply a small spot in an inconspicuous area and allow it to dry to test for color satisfaction. • Wipe off the excess material in the direction of the wood grain before it dries.
--

RECOMMENDED PRIMERS	None	RECOMMENDED APPLICATION	Cloth: As supplied Brush: As supplied Roller: Not recommended Spray: Not recommended Airless: As supplied
APPLICATION TEMP.	Minimum: 50°F Maximum: 90°F	STORAGE TEMP.	Minimum: 60°F Maximum: 80°F
TINTING	Intermixing of colors is recommended to achieve many additional shades. May also be tinted with up to 4 fl. oz. per gallon using approved colorants.	DRYING TIME (Good Conditions)	To Recoat: 2-4 hrs. To Topcoat: 18-24 hrs. Hard: 18-24 hrs. Full Use: 5-7 days
PRACTICAL COVERAGE	400-600 sq. ft./gal. (Depends on substrate texture, porosity, and application method)	REDUCTION	Apply without thinning
RECOMMENDED FILM PER COAT	Wet: 2.6-4.2 mils Dry: 0.9-1.4 mils	CLEANUP	Mineral Spirits

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	All colors	1 Gallon	1 Quart	1 Pint
FREIGHT CLASS	Not regulated	SDS	Available upon request	