

Interior

VERSA-SEAL ACRYLIC ENAMEL UNDERCOATER

240-66

12/11/12

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> • A fast drying, waterborne primer / sealer exhibiting easy sanding and excellent holdout properties. • Causes little or no grain raising. • Minimizes gloss loss when painting over porous surfaces. • Soap and water cleanup. • Low odor / low VOC formulation (compliant for most areas) 	RECOMMENDED USES <ul style="list-style-type: none"> • Specially formulated for interior bare wood substrates including baseboards, railings, crown molding, window and door trim. • Use to create a very smooth, sealed surface for finishing with latex or oil base paints. • Also ideal for bare or previously painted drywall, plaster, and masonry surfaces.
COLORS 240-66 White	FINISH Flat VEHICLE Latex Polymers FORMULATION Formulated without lead, chrome, and mercury

PHYSICAL DATA

GLOSS RATING 2-5%	VISCOSITY 96-100 KU
PERCENT SOLIDS Weight: 51% +/- 2.0 Volume: 35% +/- 2.0	NET WT. PER GAL. 11.0 +/- 0.25 lbs./gal.
VOC CATEGORY Less than 120 grams/liter	FLASH POINT Higher than 200°F

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- New plaster and masonry should age at least 30 days before being coated.
- Joint compound must be completely dry and smooth before coating.
- Allowing additional drying time will promote easier sanding.
- A stain blocking primer or sealer is recommended on wood knots or on woods containing bleeding extractives.

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied
------------------------------------	---

APPLICATION TEMP. Minimum: 50°F Maximum: 90°F	STORAGE TEMP. Minimum: 50°F Maximum: 90°F
--	--

TINTING Up to two fluid ounces per gallon with approved colorants. The addition of colorant may extend drying times.	DRYING TIME (Good Conditions) To Sand: 1 hr. minimum To Topcoat: 1 hr. minimum Hard: 18-24 hrs.
---	---

PRACTICAL COVERAGE 300-400 sq. ft. per gallon (Depends on substrate texture and porosity)	REDUCTION Apply without thinning (Use small amounts of clean water only if necessary).
--	---

RECOMMENDED FILM PER COAT Wet: 4.0-5.3 mils Dry: 1.4-1.9 mils	CLEANUP Soap and water
--	-------------------------------

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 240-66	5 Gallon 1 Gallon 1 Quart
----------------------------------	-------------------------------------

FREIGHT CLASS Not Regulated	MSDS Available upon request
------------------------------------	------------------------------------