

Interior

VERSA-SEAL HOLDOUT DRYWALL PRIMER/SEALER

246-66

12/19/11

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> • A high quality waterborne primer specially formulated to seal porous substrates and provide a uniform surface for topcoating • Exceptional holdout • May be finished with latex or oil base paints • Soap and water cleanup • Low odor / low VOC formulation (compliant for most areas) 	RECOMMENDED USES <ul style="list-style-type: none"> • Minimizes the gloss difference of painting over porous and non-porous areas such as tape joints and other repairs compared to the bare substrate • Use on properly prepared drywall, plaster, masonry, and wood • Interior walls, ceilings, and trim • Great for sealing porous painted surfaces
COLORS 246-66 White	FINISH Flat VEHICLE Latex Polymer FORMULATION Formulated without lead, chrome, and mercury

PHYSICAL DATA

GLOSS RATING Less than 10%	VISCOSITY 95-98 KU
PERCENT SOLIDS Weight: 51% +/- 2.0 Volume: 36% +/- 2.0	NET WT. PER GAL. 10.8 +/- 0.25 lbs./gal.
VOC CATEGORY Less than 100 grams/liter	FLASH POINT Higher than 200°F

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions
- Correct for the cause of any previous paint failures before applying this product
- New plaster and masonry should age at least 30 days before being coated
- Joint compound must be completely dry and smooth before coating
- A stain blocking primer or sealer is recommended on wood knots or on woods containing bleeding extractives

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied
------------------------------------	---

APPLICATION TEMP. Minimum: 50°F Maximum: 90°F	STORAGE TEMP. Minimum: 50°F Maximum: 90°F
--	--

TINTING Not to be tinted	DRYING TIME Tack Free: 30-60 min. (Good Conditions) To Recoat: 1-2 hrs. Hard: 18-24 hrs.
---------------------------------	--

PRACTICAL COVERAGE 400 sq. ft./gal. (Depends on substrate texture and porosity)	REDUCTION Apply without thinning (Use small amounts of clean water only if necessary)
---	--

RECOMMENDED FILM PER COAT Wet: 3.5-4.0 mils Dry: 1.3-1.5 mils	CLEANUP Soap and water
---	-------------------------------

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 246-66	5 Gallon	1 Gallon	1 Quart
----------------------------------	----------	----------	---------

FREIGHT CLASS Not Regulated	MSDS Available upon request
------------------------------------	------------------------------------