



TECHNICAL DATA SHEET

Interior/Exterior

VERSA-SEAL ALKYD STAIN BLOCK

249-88

11/19/2010

PRODUCT CHARACTERISTICS

| | |
|---|--|
| DESCRIPTION <ul style="list-style-type: none"> • A fast drying alkyd primer formulated to block stains and provide a sound surface for painting • Seals out water and smoke stains • Seals fire damaged substrates • Seals out ink pen, marker, crayon, tannins, and many other stains • Low VOC formulation (compliant for most areas) | RECOMMENDED USES <ul style="list-style-type: none"> • May be used on interior drywall, plaster, wood, aluminum and ferrous metal substrates • Suitable for exterior wood surfaces • May be applied to the bare substrates or over most existing coatings • May be finished with latex or oil base paints • Not designed to block tar or asphalt stains |
| COLORS 249-88 White | FINISH Flat VEHICLE Modified Alkyd FORMULATION Formulated without lead, chrome and mercury |

PHYSICAL DATA

| | |
|---|---|
| GLOSS RATING <10% | VISCOSITY 68-72 KU |
| PERCENT SOLIDS Weight: 73% ± 2.0 Volume: 52% ± 2.0 | NET WT/GAL 11.9 ± 0.25 lbs./gal. |
| VOC CATEGORY Less than 350 grams/liter | FLASH POINT 55°F |

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- Remove as much of the stain as possible prior to priming.
- Although this product may be recoated in 30-45 minutes under good conditions, allowing it to dry overnight can help in blocking difficult stains.
- Severe stains may require a second coat in order to achieve complete sealing.
- A Defi-Rust Oil Base Metal Primer is recommended as the first coat on bare metal for added corrosion resistance.

| | |
|---|---|
| RECOMMENDED PRIMERS None | RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied |
| APPLICATION TEMP. Minimum: 50°F Maximum: 90°F | STORAGE TEMP. Minimum: 50°F Maximum: 90°F |
| TINTING Not to be tinted - Tinting may compromise stain blocking properties | DRYING TIME (Good Conditions) To Recoat: 30-45 minutes Hard: 18-24 hours |
| PRACTICAL COVERAGE 400-500 sq. ft./gal. (Depends on substrate texture and porosity) | REDUCTION Apply without thinning |
| RECOMMENDED FILM PER COAT Wet: 3.2-4.0 mils Dry: 1.6-2.0 mils | CLEANUP Mineral Spirits or VM&P Naphtha |

PACKAGING AND DISTRIBUTION

| | |
|--------------------------------------|-------------------------------------|
| STANDARD PACKAGING 249-88 | 5 Gallon 1 Gallon 1 Quart |
| FREIGHT CLASS Flammable Paint | MSDS Available upon request |

A division of the Harrison Paint Co. • 1329 Harrison Ave SW, Canton, OH 44706
 Phone: (330) 455-5125 • Customer Service: 1-800-321-0680 • Fax: (330) 454-1750