Dutch Standard Paints and Specialty Products

TECHNICAL DATA SHEET

Exterior

VERSA-SEAL ACRYLIC LATEX WOOD PRIMER 250-77

10/9/15

PRODUCT CHARACTERISTICS

DESCRIPTION	RECOMMENDED USES
• A high quality, waterborne primer specially formulated to seal bare wood surfaces. • Excellent stain blocking properties. • Breathable film resists blistering and peeling. • Outstanding base coat for finishing with latex house paints. • Soap and water cleanup. • Low odor / low VOC formulation (compliant for most areas).	• Use to prime bare pine, cedar, redwood, pressure-treated lumber and other wood species. • Great for new wood or spot priming previously painted surfaces. • Ideal for wood siding, trim, shakes, shingles, and plywood found on homes, barns, sheds, gazebos, fences and other structures. • May be used to block stains on previously painted surfaces that have been properly prepared.
COLORS 250-77 White	**FINISH** Low Sheen **VEHICLE** Acrylic Polymer **FORMULATION** Formulated without lead, chrome, and mercury

PHYSICAL DATA

GLOSS RATING	Less than 15%	**VISCOSITY**	92-96 KU
PERCENT SOLIDS	Weight: 53% +/- 2.0 Volume: 40% +/- 2.0	**NET WT. PER GAL.**	10.7 +/- 0.25 lbs./gal.
VOC CATEGORY	Less than 50 grams/liter	**FLASH POINT**	Higher than 200°F

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- May be topcoated in one hour for general priming under good conditions. Allow a minimum of two hours dry before topcoating for stain blocking.
- Allowing the primer a longer dry time (up to 18 hours) before topcoating will improve the stain blocking properties.
- For best results on severe stains, apply a second coat of primer a minimum of 4 hours after the initial coat and allow it to dry18-24 hours before topcoating.

RECOMMENDED PRIMERS	RECOMMENDED APPLICATION
None	Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied

APPLICATION TEMP.	Minimum: 50°F Maximum: 90°F	**STORAGE TEMP.**	Minimum: 50°F Maximum: 90°F

TINTING	May be tinted with approved colorants up to two fluid ounces per gallon. (The addition of tinting colorants may adversely impact stain blocking)	**DRYING TIME (Good Conditions)**	Tack Free: To Recoat: Hard:	30 min. 1 hrs. 18-24 hrs.

PRACTICAL COVERAGE	300-400 sq. ft./gal. (Depends on substrate texture and porosity)	**REDUCTION**	Apply without thinning. Use small amounts of clean water only if necessary. (The addition of water may adversely impact stain blocking)

RECOMMENDED FILM PER COAT	Wet: Dry:	4.0-5.3 mils 1.6-2.1 mils	**CLEANUP**	Soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	250-77	White	5 Gallon	1 Gallon	1 Quart

FREIGHT CLASS	Not Regulated	**MSDS**	Available upon request

A division of the Harrison Paint Co. ● 1329 Harrison Ave SW, Canton, OH 44706
Phone: (330) 455-5125 ● Customer Service: 1-800-321-0680 ● Fax: (330) 454-1750