

Interior

**PRO-STANDARD 2000 LATEX FLAT WALL PAINT****300-01**

8/31/11

**PRODUCT CHARACTERISTICS**

<b>DESCRIPTION</b>	<b>RECOMMENDED USES</b>
<ul style="list-style-type: none"> <li>• A high quality wall and ceiling paint designed for the professional</li> <li>• Excellent hide and touchup</li> <li>• Flat finish helps hide imperfections and glare</li> <li>• Low odor and fast dry</li> <li>• Spatter resistant</li> <li>• Low VOC formulation (compliant for most areas)</li> </ul>	<ul style="list-style-type: none"> <li>• Designed for use on interior drywall, plaster, wood, masonry, and primed metal surfaces</li> <li>• Ideal for living rooms, dining rooms, bedrooms, closets, ceilings and any area where a tough flat finish is desired</li> <li>• Not for use on tub or shower stalls, floors, or any surface that will be under water</li> </ul>
<b>COLORS</b>	<b>FINISH</b>
300-01 Wall and Ceiling White      300-93 Mid Tone Base	Flat
300-06 Antique White                300-94 Deep Tint Base	<b>VEHICLE</b>
300-92 Light Tint Base	Latex Polymer
	<b>FORMULATION</b>
	Formulated without lead, chrome and mercury

**PHYSICAL DATA (Mixed Components)**

<b>GLOSS RATING</b>	1-3%	<b>VISCOSITY</b>	110-112 KU
<b>PERCENT SOLIDS</b>	Weight: 56% ± 2.0      Volume: 37% ± 2.0	<b>NET WT/GAL</b>	12.0± 0.25 lbs./gal.
<b>VOC CATEGORY</b>	Less than 100 grams/liter	<b>FLASH POINT</b>	Higher than 200°F (Setaflash)

**SURFACE PREPARATION & APPLICATION INSTRUCTIONS**

<ul style="list-style-type: none"> <li>• Read label directions for detailed instructions.</li> <li>• Correct for the cause of any previous paint failures before applying this product.</li> <li>• New masonry should age at least 30 days before being painted.</li> <li>• A Versa-Seal stain blocking primer is recommended as a first coat on wood containing bleeding extractives (follow label instructions).</li> <li>• Bare metal must first be primed with a Defi-Rust Acrylic Primer before applying this product (follow label instructions).</li> </ul>
--

<b>RECOMMENDED PRIMERS</b>	<b>RECOMMENDED APPLICATION</b>
Drywall                    342-66 Pro-Standard 2000 Latex Primer	Brush:                    As supplied
Plaster                    342-66 Pro-Standard 2000 Latex Primer	Roller:                    As supplied
Masonry                 342-66 Pro-Standard 2000 Latex Primer	Spray:                    Up to 10:1 reduction with clean water
Wood                     342-66 Pro-Standard 2000 Latex Primer	Airless:                    As supplied
Metal                    622-XX Defi-Rust Acrylic Metal Primer	
<b>APPLICATION TEMP.</b>	<b>STORAGE TEMP.</b>
Minimum: 50°F      Maximum: 90°F	Minimum: 50°F      Maximum: 90°F
<b>TINTING</b>	<b>DRYING TIME</b>
Bases may be tinted with approved colorants	Tack Free:                1 hr.
	(Good Conditions) To Recoat:                2-4 hrs.
	Hard:                      18-24 hrs.
<b>PRACTICAL COVERAGE</b>	<b>REDUCTION</b>
300-400 sq. ft./gal. (excludes spray loss)	Apply without thinning (Use small amounts of clean water only if necessary)
Depending on surface texture and porosity	
<b>RECOMMENDED FILM PER COAT</b>	<b>CLEANUP</b>
Wet: 4.0-5.3 mils	Soap and water
Dry: 1.5-2.0 mils	

**PACKAGING AND DISTRIBUTION**

<b>STANDARD PACKAGING</b>	300-01 All colors and bases	5 Gallon                1 Gallon 5 Gallon                1 Gallon
<b>FREIGHT CLASS</b>	Not regulated	<b>MSDS</b> Available upon request