

Interior

## PRO-STANDARD 2000 LATEX SEMI-GLOSS WALL PAINT

306-01

8/31/11

### PRODUCT CHARACTERISTICS

<b>DESCRIPTION</b> <ul style="list-style-type: none"> <li>• A high quality, semi-gloss wall paint designed for the professional</li> <li>• Excellent hide</li> <li>• Smooth enamel-like finish</li> <li>• Low odor and fast dry</li> <li>• Spatter resistant</li> <li>• Low VOC formulation (compliant for most areas)</li> </ul>	<b>RECOMMENDED USES</b> <ul style="list-style-type: none"> <li>• Designed for use on interior drywall, plaster, wood, masonry, and primed metal surfaces</li> <li>• Ideal for kitchen, bathroom, laundry room, and closet walls</li> <li>• Great for woodwork, trim, doors, and any area where a tough semi-gloss finish is desired</li> <li>• Not for use on tub or shower stalls, floors, or any surface that will be under water</li> </ul>
<b>COLORS</b> 306-01 White                      306-93 Mid Tone Base 306-06 Antique White        306-94 Deep Tint Base 306-92 Light Tint Base	<b>FINISH</b> Semi-Gloss  <b>VEHICLE</b> Latex Polymer  <b>FORMULATION</b> Formulated without lead, chrome and mercury

### PHYSICAL DATA (Mixed Components)

<b>GLOSS RATING</b> 45-55% <b>PERCENT SOLIDS</b> Weight: 44% ± 2.0      Volume: 30% ± 2.0 <b>VOC CATEGORY</b> Less than 150 grams/liter	<b>VISCOSITY</b> 105-108 KU <b>NET WT/GAL</b> 10.4± 0.25 lbs./gal. <b>FLASH POINT</b> Higher than 200°F (Setaflash)
---	---

### SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- New masonry should age at least 30 days before being painted.
- A Versa-Seal stain blocking primer is recommended as a first coat on wood containing bleeding extractives (follow label instructions).
- Bare metal must first be primed with a Defi-Rust Acrylic Primer before applying this product (follow label instructions).

<b>RECOMMENDED PRIMERS</b> Drywall                      342-66 Pro-Standard 2000 Latex Primer Plaster                        342-66 Pro-Standard 2000 Latex Primer Masonry                      342-66 Pro-Standard 2000 Latex Primer Wood                          342-66 Pro-Standard 2000 Latex Primer Metal                          622-XX Defi-Rust Acrylic Metal Primer	<b>RECOMMENDED APPLICATION</b> Brush:                        As supplied Roller:                        As supplied Spray:                        Up to 10:1 reduction with clean water Airless:                      As supplied
<b>APPLICATION TEMP.</b> Minimum: 50°F      Maximum: 90°F	<b>STORAGE TEMP.</b> Minimum: 50°F      Maximum: 90°F
<b>TINTING</b> Bases may be tinted with approved colorants	<b>DRYING TIME (Good Conditions)</b> Tack Free:                    1 hr. To Recoat:                  4-6 hrs. Hard:                         18-24 hrs.
<b>PRACTICAL COVERAGE</b> 300-400 sq. ft./gal. (excludes spray loss) Depending on surface texture and porosity	<b>REDUCTION</b> Apply without thinning (Use small amounts of clean water only if necessary)
<b>RECOMMENDED FILM PER COAT</b> Wet: 4.0-5.3 mils Dry: 1.2-1.6 mils	<b>CLEANUP</b> Soap and water

### PACKAGING AND DISTRIBUTION

<b>STANDARD PACKAGING</b> 306-01 All colors and bases	5 Gallon                      1 Gallon 5 Gallon                      1 Gallon
<b>FREIGHT CLASS</b> Not regulated	<b>MSDS</b> Available upon request