



TECHNICAL DATA SHEET

PRO-STANDARD 2000

Interior

INTERIOR PVA PRIMER

342-66

03/03/2003

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> • A professional quality white latex wall sealer for interior plaster, drywall, and masonry. • Can be top-coated with oil or latex paints. • Low VOC & fast dry. • Soap & water cleanup. 	RECOMMENDED USES <ul style="list-style-type: none"> • Recommended for priming and sealing interior plaster, drywall, or masonry. • Not intended to be used as a finish coat. • Do not mix with oil colors, other paints, or solvents. 						
COLORS 342-66 White	<table border="0"> <tr> <td>FINISH</td> <td>Flat</td> </tr> <tr> <td>VEHICLE</td> <td>Latex Emulsion</td> </tr> <tr> <td>FORMULATION</td> <td>Lead, chromate, and mercury free</td> </tr> </table>	FINISH	Flat	VEHICLE	Latex Emulsion	FORMULATION	Lead, chromate, and mercury free
FINISH	Flat						
VEHICLE	Latex Emulsion						
FORMULATION	Lead, chromate, and mercury free						

PHYSICAL DATA

GLOSS RATING Flat	VISCOSITY 100-105 K.U.
PERCENT SOLIDS By weight: 45.5 ± 2.0% By volume: 29.0 ± 2.0%	NET WT. PER GAL. 10.8 ± 0.25 lbs./gal.
VOC CATEGORY 2.1 lbs./gal. (250 grams/liter)	FLASH POINT >200 ° F Closed Cup

SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting.
- New plaster or masonry surfaces should age at least 30 days before being painted.
- All repairs, patching, and sanding should be done before primer is applied.
- This product can be top-coated after four to six hours under normal drying conditions. One coat of this product is usually sufficient on most surfaces.

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: Up to 10:1 reduction with clean water Airless: As supplied
APPLICATION TEMPERATURE Minimum: 50 °F. Maximum: 90 °F.	STORAGE TEMPERATURE Minimum: 35 °F. Maximum: 120 °F.
TINTING May be tinted to pastel shades with approved colorants up to 4 oz. per gallon. The addition of tinting colorants may extend dry times.	DRYING TIME (Good Conditions) Tack free: 1 hrs. To recoat: 2-4 hrs. Hard: 24 hrs.
PRACTICAL COVERAGE 300-400 sq. ft./gal. (Depending upon the porosity of the substrate)	REDUCTION Not normally recommended. If necessary use small amounts of clean water. (For spray reduction see recommended application)
RECOMMENDED FILM PER COAT Wet: 3.0-4.0 mils Dry: 1.0-1.2 mils	CLEAN-UP Clean up with soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 342-66	5 Gallon Gallon
FREIGHT CLASS Non-Flammable Paint	MSDS Available upon request.

HPF-0054, Rev. 1, 8/21/98