Dutch Standard Paints and Specialty Products

TECHNICAL DATA SHEET

Exterior

COUNTRY ESTATE LATEX BARN & FENCE PAINT 704-01

3/22/2010

PRODUCT CHARACTERISTICS

DESCRIPTION	RECOMMENDED USES
• A waterborne coating designed to protect and beautify wood, masonry and primed metal surfaces • Flexible and breathable to resist blistering and peeling • Dried film is weather and mildew resistance • Soap and water cleanup • Low VOC formulation (compliant for most areas)	• Ideal for use on barns, silos, sheds, fences, masonry walls and many other structures • Not for use on horizontal surfaces where water collects • May be applied directly on bare wood and masonry surfaces or after priming • Bare metal must be primed

COLORS		
704-01 White 704-02 Black 704-32 Red	**FINISH** **VEHICLE** **FORMULATION**	Low Lustre Latex Polymer Formulated without lead, chrome and mercury

PHYSICAL DATA (Mixed Components)

GLOSS RATING	10-20%	**VISCOSITY**	105-108 KU
PERCENT SOLIDS	Weight: 35% ± 2.0 Volume: 21% ± 2.0	**NET WT/GAL**	10.0 ± 0.25 lbs./gal.
VOC CATEGORY	Less than 100 grams/liter	**FLASH POINT**	Higher than 200°F (Setaflash)

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

- Read label directions for detailed instructions.
- Correct for the cause of any previous paint failures before applying this product.
- New masonry should age at least 30 days before being painted.
- Bare metal must first be primed with a Defi-Rust Acrylic Primer before applying this product (follow label instructions).

RECOMMENDED PRIMERS	
Wood	Direct Application
Metal	622-XX Defi-Rust Acrylic Metal Primers
Galvanizing	622-XX Defi-Rust Acrylic Metal Primers
Masonry	Direct Application

RECOMMENDED APPLICATION	
Brush:	As supplied
Roller:	As supplied
Spray:	As supplied
Airless:	As supplied

APPLICATION TEMP.	Minimum: 50°F	Maximum: 90°F	**STORAGE TEMP.**	Minimum: 50°F	Maximum: 90°F
TINTING	Not to be tinted		**DRYING TIME (Good Conditions)**	Tack Free: To Recoat: Hard:	1 hr. 2-4 hrs. 18-24 hrs.
PRACTICAL COVERAGE	400 sq. ft./gal. (250-300 on very porous wood) (Depends on substrate texture and porosity)		**REDUCTION**	Apply without thinning (Use small amounts of clean water only if necessary)	
RECOMMENDED FILM PER COAT	Wet: 3.8-4.2 mils Dry: 0.9-0.9 mils		**CLEANUP**	Soap and water	

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	704-01	704-02	704-32	5 Gallon	1 Gallon Kit
FREIGHT CLASS	Not regulated			**MSDS**	Available upon request

A division of the Harrison Paint Co. ● 1329 Harrison Ave SW, Canton, OH 44706
Phone: (330) 455-5125 ● Customer Service: 1-800-321-0680 ● Fax: (330) 454-1750