



# TECHNICAL DATA SHEET

Exterior

**WOODUCK EXTERIOR ACRYLIC SOLID-HIDE STAIN**

**830-01**

08/14/2001N

Formerly 1120

## PRODUCT CHARACTERISTICS

<b>DESCRIPTION</b> <ul style="list-style-type: none"> <li>A solid-hide exterior stain for use on both bare and previously stained wood surfaces.</li> <li>Provides a decorative and protective coating without altering the natural texture of the wood.</li> <li>Resists mildew, peeling, blistering, and UV degradation.</li> <li>Soap &amp; water cleanup.</li> </ul>			<b>RECOMMENDED USES</b> <ul style="list-style-type: none"> <li>Recommended for smooth or rough sawn siding, shakes, shingles, plywood, and many other similar wood surfaces.</li> <li>Not for use on decks or other high traffic areas.</li> <li>Do not mix with oil colors, other paints, or solvents.</li> <li>Not to be used as a clear coating.</li> </ul>	
<b>COLORS</b> 830-01 White      830-92 LTB      830-95 CLB 830-02 Ebony      830-93 MTB      830-98 UDB 830-36 Navajo Red      830-94 DTB 830-37 Oxford Brown			<b>FINISH</b> Flat  <b>VEHICLE</b> Acrylic Latex  <b>FORMULATION</b> Lead, chromate, and mercury free	

## PHYSICAL DATA

<b>GLOSS RATING</b>	Flat	<b>VISCOSITY</b>	88-92 K.U.
<b>PERCENT SOLIDS</b>	By weight: 47.1 ± 2.0% By volume: 35.5 ± 2.0%	<b>NET WT. PER GAL.</b>	10.6 ± 0.25 lbs./gal.
<b>VOC CATEGORY</b>	2.9 lbs./gal. (350 grams/liter)	<b>FLASH POINT</b>	156 ° F Closed Cup

## SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting.
- The use of the recommended primer is suggested when staining over redwood or cedar which contain bleeding oils.
- Previously stained surfaces should be cleaned, patched, and spot-primed as needed then top-coated as indicated for unstained surfaces. Weathered surfaces in poor condition require the removal of old paint and a prime coat.
- For optimum results, two coats of this product is recommended.

<b>RECOMMENDED PRIMERS</b> Wood      250-77 Versa Seal Acrylic Wood Primer		<b>RECOMMENDED APPLICATION</b> Brush:      As supplied Roller:      As supplied Spray:      As supplied Airless:      As supplied	
<b>APPLICATION TEMPERATURE</b> Minimum: 50 °F. Maximum: 90 °F.		<b>STORAGE TEMPERATURE</b> Minimum: 35 °F. Maximum: 120 °F.	
<b>TINTING</b> Hundreds of additional colors may be obtained by using the tint bases and approved colorants.		<b>DRYING TIME (Good Conditions)</b> Tack free:      1 hrs. To recoat:      2 hrs. Hard:      24 hrs.	
<b>PRACTICAL COVERAGE</b> 300-400 sq. ft./gal. (Depending upon the porosity of the substrate)		<b>REDUCTION</b> Not normally recommended. If necessary use small amounts of clean water. (For spray reduction see recommended application)	
<b>RECOMMENDED FILM PER COAT</b> Wet:      3.0-4.0 mils Dry:      1.0-1.5 mils		<b>CLEAN-UP</b> Clean up with soap and water	

## PACKAGING AND DISTRIBUTION

<b>STANDARD PACKAGING</b>	830-01	5 Gallon	Gallon
	All Tint Bases	5 Gallon	Gallon
	All Standard Colors		Gallon
<b>FREIGHT CLASS</b>	Non-Flammable Paint		<b>MSDS</b> Available upon request.

HPF-0054, Rev. 1, 8/21/98