Dutch Standard Paints and Specialty Products

TECHNICAL DATA SHEET

Exterior

WOODUCK EXTERIOR ACRYLIC DECK STAIN

834-96

08/14/2001C

Formerly 1171

PRODUCT CHARACTERISTICS

DESCRIPTION	**RECOMMENDED USES**
• An exterior stain for use on wooden decks that withstands foot traffic. • Provides a decorative and protective coating without altering the natural texture of the wood or completely obscuring the grain. • Resists mildew, peeling, blistering, and UV degradation. • Soap & water cleanup.	• Recommended for use on wood decks, railings, gazebos, and other exterior wooden surfaces. • Can be used as a clear coating. • Requires no weathering period when used on new construction. • Do not mix with oil colors, other paints, or solvents.
COLORS 834-96 CLB	**FINISH** Satin **VEHICLE** Acrylic Latex **FORMULATION** Lead, chromate, and mercury free

PHYSICAL DATA

GLOSS RATING	Satin	**VISCOSITY**	35-45 seconds Zahn #2
PERCENT SOLIDS	By weight: 28.4 ± 2.0% By volume: 24.6 ± 2.0%	**NET WT. PER GAL.**	9.0 ± 0.25 lbs./gal.
VOC CATEGORY	2.9 lbs./gal. (350 grams/liter)	**FLASH POINT**	142 ° F Closed Cup

SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- All surfaces must be clean and free of dust, dirt, grease, mildew, soap residue, loose paint, glue size and any other foreign matter. For best results, the cause of any previous paint failure should be corrected before repainting. All previous water repellancy must be removed prior to application.
- No primer is recommended as this will affect the transparency of the stain. One coat of this product is usually sufficient on most surfaces. If two coats are desired, a wet-on-wet application is necessary.
- Previously stained surfaces need to be clean prior to application; a light sanding is recommended to unsure adhesion of the new coat. Covering a previous color of semi-transparent stain will affect the resulting color appearance. It is recommended that the stain be tested in an inconspicuous area for color determination. Do not puddle stain on.
- Surfaces stained with this product can be walked on after 24 hours drying time under good conditions. Optimum UV and weathering resistance of this product is achieved when it is tinted.

RECOMMENDED PRIMERS	**RECOMMENDED APPLICATION**
None	Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied
APPLICATION TEMPERATURE Minimum: 50 °F. Maximum: 90 °F.	**STORAGE TEMPERATURE** Minimum: 35 °F. Maximum: 120 °F.
TINTING Hundreds of additional colors may be obtained by using the tint bases and approved colorants.	**DRYING TIME (Good Conditions)** Tack free: 1 hrs. To recoat: 10-15 min. Hard: 12 hrs.
PRACTICAL COVERAGE 200-400 sq. ft./gal. (Depending upon the porosity of the substrate)	**REDUCTION** Not normally recommended. If necessary use small amounts of clean water. (For spray reduction see recommended application)
RECOMMENDED FILM PER COAT Wet: 3.0-4.0 mils Dry: 0.8-1.0 mils	**CLEAN-UP** Clean up with soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING	834-95	5 Gallon	Gallon
FREIGHT CLASS	Non-Flammable Paint	**MSDS**	Available upon request.

HPF-0054, Rev. 1, 8/21/98

A division of the Harrison Paint Co. • P.O. Box 8470 Canton, OH 44711
Phone: (330) 455-5125 Customer Service: 1-800-321-0680 Fax: (330) 454-1750