



TECHNICAL DATA SHEET

Exterior

ALKYD TRAFFIC ZONE MARKING PAINT

921-01

08/14/2001U

Formerly 333

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> A alkyd paint formulated for marking traffic zones of parking lots. One gallon provides 1,000 feet of four inch line. White is tintable to light blue for handicap marking. 	RECOMMENDED USES <ul style="list-style-type: none"> Recommended for marking of parking lots, driveways, walkways, and curbs of asphalt or concrete. Do not mix with water or other paint products.
COLORS 921-01 White 921-33 Yellow	FINISH Flat VEHICLE Alkyd FORMULATION Lead, chromate, and mercury free

PHYSICAL DATA

GLOSS RATING Flat PERCENT SOLIDS By weight: 68.0 ± 2.0% By volume: 43.8 ± 2.0% VOC CATEGORY 3.8 lbs./gal. (450 grams/liter)	VISCOSITY 65-67 K.U. NET WT. PER GAL. 11.7 ± 0.25 lbs./gal. FLASH POINT 50 ° F Closed Cup
--	--

SURFACE PREPERATION & APPLICATION INSTRUCTIONS

- Make sure all surfaces are reasonably clean and free of surface contaminants.
- New concrete should be allowed to cure for 30 days before being painted; asphalt requires 90 days.
- Do not apply if rain is forcasted within 24 hours.
- Surfaces are dry for foot or vehicle traffic after 12 hours under good drying conditions.

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied
APPLICATION TEMPERATURE Minimum: 50 °F. Maximum: 90 °F.	STORAGE TEMPERATURE Minimum: 35 °F. Maximum: 120 °F.
TINTING White may be tinted to pastel shades with approved colorants up to 4oz. per gallon.	DRYING TIME (Good Conditions) Tack free: 30 min. To recoat: 2 hrs. Hard: 12 hrs.
PRACTICAL COVERAGE 1,000 ft. of 4 inch line per gal.	REDUCTION As supplied (For spray reduction, see recommended application)
RECOMMENDED FILM PER COAT Wet: 4.8-5.0 mils Dry: 2.0-2.2 mils	CLEAN-UP Clean up with VM & P Naptha or Xylol

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 921-01, 921-33	5 Gallon Gallon
FREIGHT CLASS Flammable Paint	MSDS Available upon request.

HPF-0054, Rev. 1, 8/21/98