



## TECHNICAL DATA SHEET

### ACRYLIC URETHANE WATER EMULSION FINISH

197-1256

#### DESCRIPTION

This water borne acrylic urethane emulsion is designed for high performance uses where hardness, flexibility, and abrasion resistance are required. Recommended primarily for concrete, quarry tile, terrazzo brick, and synthetic surfaces. It is a product, which meets ecological standards, is easy to apply, and equipment can be cleaned with detergent and water.

#### PRODUCT CHARACTERISTICS

- ◆ Durability
- ◆ Ease of Application
- ◆ Abrasion, Chemical, Solvent & Water Resistant
- ◆ Fast Drying
- ◆ Non-Flammable
- ◆ Minimum down time - cures in four hours
- ◆ Mild pleasant odor

#### METHOD OF APPLICATION

Clean floor thoroughly. Remove previous finish, dirt, dust, etc. Rinse clean and let dry. Pour finish into a shallow container. Use lambs wool applicator or a cotton mop. Apply in thin coats. Drying time is approximately 60 minutes, depending on the thickness of the film. Second coat may be applied after 90 minutes. Hardens overnight. Water Borne Acrylic Urethane can only be removed with H.D.W.B. Stripper.

#### TECHNICAL DATA

Weight per Gallon .....	8.5 pounds
Color .....	Milky White
Solids .....	25%
pH .....	8.5 Typical
Freeze/Thaw Stability .....	Passes 2 cycles
Coverage Concrete .....	300 - 500 sq. ft. per gallon
Monolithic Sports Floor .....	400 - 600 sq. ft. per gallon
Flash Point C.O.C. ....	None

#### AVAILABLE CONTAINER SIZES

55 Gallon, 5 Gallon and 1 Gallon Containers

The information and data given herein are based upon tests and reports considered reliable and believed to be accurate. However, due to circumstances beyond our control including but not limited to surface preparation, application technique, substrate and curing conditions, no guarantee of duplicate performance, expressed or implied, is made.