



## TECHNICAL DATA SHEET

### HIGH GLOSS SEALER & FINISH

**197-4318 & 197-4325**

#### DESCRIPTION

A heavy-duty urethane fortified, water-base acrylic that provides a high gloss/wet look and excellent durability. Designed as a sealer for bare concrete floors or as a finish for vinyl or rubber tile.

#### PRODUCT CHARACTERISTICS

- ◆ Transparent high gloss
- ◆ Will not darken with age
- ◆ Water resistant
- ◆ Recoats easily
- ◆ Extremely durable
- ◆ Buffable
- ◆ Removable with standard strippers
- ◆ Helps prevent concrete dusting

#### METHOD OF APPLICATION

Remove old finish and clean floor thoroughly before applying new finish. Apply finish using spray, roller, brush, lamb's wool applicator or cotton mop. Do not agitate. Dries in 30 minutes. Allow one hour between coats.

#### TECHNICAL DATA

Solids .....	18 - 25%
PH .....	8.6
Weight per Gallon .....	8.6 pounds
Discoloration of Rubber Tile .....	None
Discoloration of Vinyl Tile .....	None
Freeze-Thaw Stability .....	Passes - 2 cycles
Coverage .....	250-1000 sq.ft.per gal.

#### AVAILABLE CONTAINER SIZES

55 Gallon, 5 Gallon and 1 Gallon Containers

#### CUSTOMIZED SOLIDS FORMULAS AVAILABLE BY SPECIAL ORDER

The information and data given herein are based upon tests and reports considered reliable and believed to be accurate. However, due to circumstances beyond our control including but not limited to surface preparation, application technique, substrate and curing conditions, no guarantee of duplicate performance, expressed or implied, is made.