



TECHNICAL DATA SHEET

Interior/Exterior

WATERBORNE ACRYLIC SWIMMING POOL PAINT

708-01

10/1/15

PRODUCT CHARACTERISTICS

DESCRIPTION <ul style="list-style-type: none"> • A water-thinnable coating designed to protect and beautify concrete, masonry, gunite, and other masonry surfaces • Outstanding performance against mild acids, alkalis, and other pool chemicals in fresh or salt water • Tough satin finish resists abrasion, weathering, and cleaning • Low VOC formulation (compliant for most areas) 	RECOMMENDED USES <ul style="list-style-type: none"> • Ideal for use on residential and commercial swimming pools, non-potable fountains and other masonry surfaces • May be applied to bare masonry or as a recoat over itself • Not for use on metal, fiberglass, or vinyl lined pools • Do not use over epoxy, urethane, chlorinated rubber or other impervious coatings or rubber base paints
COLORS 708-01 White 708-02 Black 708-30 Aquamarine 708-31 Ocean Blue	FINISH Satin VEHICLE Acrylic Polymer FORMULATION Formulated without lead, chrome and mercury

PHYSICAL DATA

GLOSS RATING 15-25%	VISCOSITY 90-95 KU
PERCENT SOLIDS Weight: 50% ± 2.0 Volume: 36% ± 2.0	NET WT/GAL 10.5 ± 0.25 lbs./gal.
VOC CATEGORY Less than 150 grams/liter	FLASH POINT 168°F (Setaflash)

SURFACE PREPARATION & APPLICATION INSTRUCTIONS

<ul style="list-style-type: none"> • Read label directions for detailed instructions. • Correct for the cause of any previous paint failures before applying this product. • New masonry should age at least 60 days before being painted. • Allow pool to dry for 7 days after draining before surface preparation. • Allow paint to cure for 7 days before filling pool with water. • CAUTION: Surface contaminations such as oil, grease, suntan lotion, water as well as other materials, may cause a hazardous slippery surface requiring caution in preventing injury.
--

RECOMMENDED PRIMERS None	RECOMMENDED APPLICATION Brush: As supplied Roller: As supplied Spray: As supplied Airless: As supplied
APPLICATION TEMP. Minimum: 50°F Maximum: 90°F	STORAGE TEMP. Minimum: 50°F Maximum: 90°F
TINTING Not to be tinted	DRYING TIME Tack Free: 1 hr. (Good Conditions) To Recoat: 4-8 hrs. Hard: 24 hrs. (7 days to fill)
PRACTICAL COVERAGE 350-400 sq. ft./gal. (Depends on substrate texture and porosity)	REDUCTION Apply without thinning - Clean water sparingly only if needed
RECOMMENDED FILM PER COAT Wet: 4.0-4.6 mils Dry: 1.5-1.7 mils	CLEANUP Soap and water

PACKAGING AND DISTRIBUTION

STANDARD PACKAGING 708-01 708-02, 708-30, 708-31	5 Gallon 1 Gallon 1 Gallon
FREIGHT CLASS Combustible Paint	MSDS Available upon request

A division of the Harrison Paint Co. • 1329 Harrison Ave SW, Canton, OH 44706
 Phone: (330) 455-5125 • Customer Service: 1-800-321-0680 • Fax: (330) 454-1750