



TECHNICAL DATA SHEET

ACRYLIC D.R. SUPER GLOSS FINISH

197-4518 & 197-4525

DESCRIPTION

A new floor finish which is a metal crosslinked acrylic copolymer. Formulated with quality and economy in mind. Recommended for its excellent gloss and ease of recoatability. This product can be used for industrial as well as institutional applications.

PRODUCT CHARACTERISTICS

- ◆ High Gloss
- ◆ Water Resistant
- ◆ Recoats Easily
- ◆ Durable - Detergent Resistant
- ◆ Non Slip
- ◆ Removable with Standard Strippers
- ◆ Excellent Response to High Speed Buffing

METHOD OF APPLICATION

Floor must be thoroughly clean before applying new finish. Pour the finish into a shallow container. Use lambs wool applicator or cotton mop. Apply in thin coats. Drying time approximately 30 min. Allow one full hour or longer for drying between coats. On new or hard surfaces, one coat will give a smooth uniform high gloss. Old or porous floors (such as asphalt tile) should be sealed with an undercoater, followed by one or two coats of finish.

TECHNICAL DATA

Solids	Available in 18 & 25%
pH	8.6
Weight per Gallon	8.6 pounds
Discoloration of Rubber and Vinyl Tile	None
Freeze/Thaw Stability	Passes - 2 cycles
Coverage	1000-1500 sq.ft.per gal.

AVAILABLE CONTAINER SIZES

Gallon, 5 Gallon and 1 Gallon Containers

OTHER SOLIDS AVAILABLE BY SPECIAL ORDER

The information and data given herein are based upon tests and reports considered reliable and believed to be accurate. However, due to circumstances beyond our control including but not limited to surface preparation, application technique, substrate and curing conditions, no guarantee of duplicate performance, expressed or implied, is made.